

RealPass-N

Compact Full-page Document Reader



RealPass-N is a compact, full-page and multi-functional document reader for one-step reading of multiple document types including ICAO standard documents such as e-Passport, e-Visa, ID cards and 1D & 2D barcodes. It is designed to capture or extract data from visual data page and RFID chip of electronic documents quickly and reliably in a variety of public and commercial sectors. By design and performance innovation, it provides 500DPI high resolution, USB3.0 interface, tempered glass with IP54 surface and Anti-glare technology to capture image and data in multiple illuminations(White, IR, UV). RealPass-N is an ideal and ergonomic form factor with low profile and simple shape for space-saving and easy integration in self-service kiosks, e-gates and counters.



RealPass-N

Compact Full-page Document Reader

FEATURES

- Compact, full-page and multi-functional document reader
- One-step reading of visual data page and RFID chip of e-documents
- ICAO Doc 9303 Standard Compliance
- 500DPI high resolution(Configurable), 24bit true color image
- OCR data capture of the Machine Readable Zone(MRZ)
- Reads ISO14443 Type A/B contactless chip, 1D/2D Barcodes
- Multiple illumination(White, IR and UV)
- Hoodless Operation in various environments
- Anti-Glare Technology to capture high quality images
- Automatic document placement detection
- Smart power consumption is automatically activated once PC turned off
- Multi-color LED and beep sound for intuitive user interface
- USB 2.0 high speed interface
Integrated USB 3.0 Hub – 2 ports for external peripheral device
- No moving parts, robust, minimal maintenance cost
- Rugged form factor with tempered glass and IP54 surface
- Low profile, simple shape for space-saving and easy integration
- Kensington® Security Lock, SAM Slot
- Provides SDK for easy integration into any systems

SPECIFICATIONS

Dimension(WxLxH, mm)	155 X 190 X 99.8(103.8 w/ Guide)
Active Window Size(HxV, mm)	130 X 90
Weight(kg)	1.0
Image Resolution(DPI)	500(Configurable), 5M Pixel Sensor
Illuminations	White/Visible, IR, UV(UVA)
Contactless RFID Reading	ISO14443 A/B Type(up to 848Kbps) including BAC, PA, AA, EAC, PACE and SAC, PC/SC support
Barcode Reading	1D:Code 39,93,128, 2 of 5 Interleaved, EAN, UPC 2D:PDF417, Data Matrix, QR Code, Aztec
Image Formats	BMP, PNG, JPEG
Indicators	Multi-color LED, Navigation LED, Beep(Programmable)
Operating Temperature	0°C ~ 50°C
Operating Humidity	0 to 95% (non-condensing)
IP rate	IP54(surface), Tempered glass(scratch free)
Power Supply	USB only or External power Supply(DC12V, 100-240V 50/60Hz)
Interface	USB 2.0 high speed, Integrated USB 3.0 Hub - 2 ports for external peripheral device
Operating Systems	Windows 10, 8, 7(32/64bit), Linux Ubuntu and CentOS LTS(32/64bit)
Software	SDK including DLLs with demo programs in multiple programming languages, F/W Upgrade via USB interface
Certificates	FCC, CE, KC, WEEE, RoHS, REACH

Above specs are subject to change without prior notice.

Fulcrum Biometrics Southern Africa

Block A, Regent Hill Office Park,
Corner Leslie & Turley Roads,
Lonehill, 2191, Sandton,
Gauteng, South Africa
+27 (0)11 702 8550
sales@fulcrumbiometrics.co.za
www.fulcrumbiometrics.co.za

